

The new generation lightweight core material


Distributed by Panel Systems Ltd

ThermHex is an innovative material primarily used in the production of lightweight sandwich panels. It is manufactured from polypropylene (PP) honeycomb that offers a weight saving of up to 85%, compared with other core materials, such as plywood.

Manufactured in Germany, the material is produced in a state-of-the-art, patented process which ensures rigidity in terms of its mechanical strength, as well as stability, ThermHex is resistant to chemicals and moisture. In addition, as part of ensuring ethical and sustainable sourcing of materials, it is also 100% recyclable.

ThermHex is both light in weight and strong making it suitable for a wide range of applications including automotive, truck bodies, marine, OEM, industrial equipment, water jet cutting, caravan and motorhome markets, plus many more.

ThermHex sheets are finished with a polypropylene barrier film. This film prevents resins or adhesives from leaking into the open cells during processing and assures the material remains robust. At the same time, the quantity of resin / adhesive needed for processing is kept to a minimum. The second standard surface finish is a PET non-woven material, which enables easy bonding of various types of facing materials with all common adhesives, including polyurethane based glues.



Technical Data

ThermHex is produced at a standard density of 80kg/m³ (5.0 Lbs / ft³). For applications with lower requirements to compression strength, ThermHex offers a lighter core with a density of 60kg/m³ (5.0 Lbs / ft³).

ThermHex is available in the standard sheet size of 2500mm x 1200mm or can be cut to size, if required. Bespoke sheet sizes up to 7500mm long are available subject to minimum production quantities.

ThermHex sheets can be ordered from Panel Systems Ltd and are available in the following thicknesses and weights.

Thickness (mm)	Weight (kg/m ²)	2500x1200mm sheet (kg)
3.5	0.59	1.76
6	0.75	2.24
8	1.15	3.46
10	1.17	3.51
12	1.25	3.75
15	1.63	4.88
18	1.96	5.89
20	1.98	5.95
25	2.77	8.30
28	2.77	8.30

Product Description

Standard dimensions (width x length)	1.200 mm x 2.500 mm	
Core thickness & Cell size	Core thickness (h)	Cell size (c)
	3,5 mm	3,0 mm
	5,0 / 6,0 mm	4,0 mm
	8,0 / 10,0 mm	8,0 mm
	12,0 / 15,0 / 18,0 / 20,0mm	5,0 mm
	25,0 / 28,0 mm	9,6 mm
Tolerances	Length	+ 10 / - 1 mm
	Width	+ 2 / - 1 mm
	Core thickness	+ / - 0,3 mm
	Squareness	+ / - 0,2°
Density	80 - 90 kg / m ³	
Surface finish	50 µm polypropylene Film / 40 g/m ² Polyester Nonwoven	

Physical Properties

Compressive strength	1,2 MPa (174 Psi)	ASTM C365–57
Compressive modulus	40 MPa (5.800 Psi)	ASTM C365–57
Shear strength (L-W)	0,5 MPa – 0,3 MPa (73 Psi – 44 Psi)	ASTM C273–61
Shear modulus (L-W)	15 MPa – 6 MPa (2.176 Psi – 870 Psi)	ASTM C273–61
Temperature range for processing and application (°C)	- 30 to + 80 short term to + 140	
Thermal conductivity	0,065 W / mK	
Fire-resistance	Normally inflammable (building material class B2 DIN 4102-1, respectively D according to EU classification), higher grades of fire resistance can be obtained in sandwich elements when using specialized skin materials.	
Chemical resistance	Excellent resistance to water, most acids, bases and salt solutions.	
Resistance to UV rays	Lasting UV resistance can be guaranteed in sandwich elements when using appropriate skin materials.	

Handling of ThermHex

Bonding

During bonding of the ThermHex honeycomb core it is essential to use the right adhesive. The correct adhesive should be determined by the requirements of all the sandwich components.

Laminating

ThermHex honeycomb cores can be laminated with different methods for example hand lay-up with vacuum moulding, fibre resin spray-up, vacuum or light-rtm. Possible types of resin are polyurethane, polyester, epoxy or phenol.

Spray-up

For large components or lamination of ThermHex honeycomb cores the fibre resin spray-up suits well. During this process, the merging of the compounds (resin, reactant and reinforcing fibre) as well as the deposition are done with a fibre-resin diffuser.

Forming

Besides forming with heat it is also possible to form honeycomb cores of small thickness (e.g. 3.5 – 10mm) at room temperature during curing of the skin layers with the help of pressure or vacuum.

Cutting

The cutting of ThermHex honeycomb cores is carried out with conventional tools and methods such as e.g. circular saw, CNC machining, circular knife, waterjet cutting, laser cutting, punching and so on.

Edge Closure

Depending on the kind of procedure, usage and pressure on the finished sheet, different edge closures are possible. For load application points, it is recommended to work with inserts that connect the two skin layers, in order to achieve a higher load application.



Applications

Building

- Cladding
- Partition Panels
- Wall Panelling

Industrial

- Wind Turbines
- Floating floors
- Swimming Pools
- Waterjet Cutting (sacrificial sheet)
- Boxes
- Furniture

Transport

- Trucks/Trailer Bodies
- Caravans & Leisure Vehicles
- Ambulances
- Buses
- Flooring

Yachting/Boating

- Deck Reinforcement
- Structural Walls
- Furniture
- Hull
- Interiors



For more information or to place on order, contact the sales office at
Panel Systems on 01909 774914 or email: sales@panelsystems.co.uk
www.panelsystems.co.uk

Units 6-8 Waleswood Industrial Estate, Mansfield Road, Waleswood, Sheffield S26 5PY

LIABILITY FOR DEFECTS

All information provided herein is based on our current knowledge and experience. Due to the high number of possible influences during processing and application, the information does not release the processor from the necessity of carrying out his own investigations and tests. Information contained herein and explanations provided by ThermHex Waben GmbH in connection with this printed matter does not represent acceptance of a guarantee. Guarantee statements require special explicit written declarations on behalf of ThermHex Waben GmbH to be effective. The constitutions stated in this datasheet determine the properties of the delivery item extensively and conclusively. Application suggestions do not establish assurance of suitability for the recommended application. We reserve the right to adapt the product to satisfy technical progress and new developments. We would be pleased to help with any enquiries including those related to special application issues. If the application for which our products are used is subject to statutory approval, the user is responsible for the procurement of such approval. Our recommendations do not release the user from the obligation of taking the possibility of impairments to third-party rights into account and of clarifying these if necessary. Furthermore we refer to our General Terms and Conditions, especially with regard to any possible liability for defects. If you are not in possession of our General Terms and Conditions we would be pleased to supply these on request. Contact: Panel Systems Ltd. Welland Close, Parkwood Industrial Estate, Rutland Road, Sheffield, S3 9QY. Tel: 0114 275 2881, Fax: 0114 278 6840.